

CAUTION

Damage to or improper use of the film panel may inadvertently trigger the sensor.



Introduction

Congratulations on your purchase of Shatter Alert™ glass breakage sensor. The Shatter Alert™ glass breakage sensor is a maintenance-free anti temper proof device designed to detect tempered glass breakage under the surface it is mounted on. This glass breakage sensor will detect breakage in the glass panel or puncture or penetration damage to the film panel. The Shatter Alert™ glass breakage sensor is connected to a Glass Security Controller that manages up to 8 different Shatter Alert™ glass breakage sensors

READ AND SAVE THIS

Use And Care Guide

To ensure longevity of your Shatter Alert™ glass breakage sensor:

- Do not scratch or puncture the edges of the sensor
- Do not scratch or puncture the surface of the sensor
- Do not mount objects like, stickers, suction holders, onto the sensor surface

When cleaning the window:

- Do use neutral pH, non-acid, non-alkaline or non-corrosive glass cleaners
- Do not use hard bristle cleaning tools.
- Do not attempt to soak the sensor into water- the panel is water resistant, not water proof.

Limited Warranty

Your Shatter Alert™ glass breakage sensors pertains to defects in workmanship or materials of its mechanical or electronic parts that may cause it to malfunction for a period of 1 year from date of purchase. This warranty excludes liability for failure through accident, misuse, neglect, and unauthorized modification or tampering. Glass Security is also excluded from any liability for failure of any 3rd party alarm, security system or electronic and mechanical systems attached to to the sensor. At its discretion, Glass Security will, under this warranty, repair or replace your Shatter Alert™ glass breakage sensors unit only. It does not cover the cost of replacing or repairing the window, glass pane, or surface it was mounted on. Glass Security will not entertain any refunds for non-defective product return.

Glass Breakage Sensor Specifications:

Thickness: 0.815mm

Width & Height: 100x58mm

Adhesive: High strength silicon & acrylic adhesive

Glass Security Controller

Working voltage: 9V/12V

Max number of film panel: 8

Power utilization:

- Normal: 2.02mA/24.2mW
- Triggered: 0.37mA/4.4mW
- Output(Alarm): Low, 16mA

Visit our website for assistance or email us with explanation of problem, proof of purchase and date of purchase to:

www.glass-security.com.sg

customer@glass-security.com.sg

2015 © Glass Security Pte Ltd All Rights Reserved - Specifications subject to change without prior notice

Designed & Assembled in Singapore
Materials from the USA